

LED Center Basket Troffer



project info:

project name:

model:

comment:

date:

Features

| | |
|----------------|---|
| Series | LTKE series |
| Description | LED Center Basket Troffer Kit |
| Voltage Input | Universal Input Voltage 100-277V High Voltage 347V |
| Lumen Efficacy | >125lm/w |
| CRI,Color Temp | CRI80, 3500/4000/5000 |
| Dimming | 0-10V dimmable |
| Damp Location | For dry/damp locations |
| Power Factor | >90 |
| THD | < 15% |
| L70 life span | >50000hours |
| Applications | offices,retail,schools |

Feature

LTKE series is shallow center baskets recessed direct/indirect,more energy saving, longer lifespan,better CRI compared to T5 lighting system. High lumen output performance >125 LPW . Combination of architectural modern design and high visual comfort.

Construction

Die formed of 24 gauge cold-rolled steel body body, and high reflectance baked white acrylic matte paint finish. Post painted sheet metal with high gloss baked white matte powder coating. Fully recessed luminaire fits standard T-Grid ceilings.

Electrical:

LPLK series troffer is designed to operate through the 120-277 Vac universal voltage range and Output Voltage Class 2 from 27-54V.

Optics:

Ribbed linear diffuser provides more light.

Dimming:

The driver is 0-10V dimmable (down to 10%) .

Applications:

Ideal for illuminating offices,retail,schools and hospitality areas

Order Number Logic

| Dekree Model | Series | Fixture Size | Input Voltage | Nominal Lumen | Driver Type | Color T. |
|---------------------|-------------|--------------|-----------------|---------------|--------------|--------------|
| LTKE-22UNV-33LFDBxx | LTK= | 22 = 2'x2' | UNV= 120-277VAC | 33L= 3250LM | FD= | 835= |
| LTKE-22UNV-38LFDBxx | LED TROFFER | 24 = 2'x4' | | 38L= 3780LM | Full Dimming | CRI80, 3500K |
| LTKE-22UNV-44LFDBxx | | | 347= 347VAC | 44L= 4410LM | 0-10v | 840= |
| LTKE-24UNV-43LFDBxx | E= E series | | | 43L= 4284LM | ND= | CRI80, 4000K |
| LTKE-24UNV-58LFDBxx | | | | 58L= 5796LM | Non Dimming | 850= |
| LTKE-22UNV-38LNDBxx | | | | | | CRI80, 5000K |
| LTKE-24UNV-45LNDBxx | | | | | | |
| LTKE-24UNV-64LNDBxx | | | | | | |

Product Size

| Height | Width | Depth |
|--------|--------|-------|
| 23.78" | 23.78" | 3.62" |
| 47.71" | 23.78" | 3.62" |

